



Item P20-0010

Drywall Access Doors

Designed for flush installation in drywall ceilings and walls. The flange of the door is textured and includes a bead so drywall joint compound can be applied in sufficient thickness to conceal flange. Prepunched holes in the flange provide additional "tooth" for the joint compound and facilitate fastening the flange to framing members with drywall screws. Joint compound is applied at the same time drywall joints are finished. The door is held in place by a continuous concealed piano hinge and steel cam-and-stud type catches. **Prime coated steel finish. Manufactured by Eimdor.**

Item	Description	Attributes
20-0010		Door Size W x H: 8" x 8" Wall Or Ceiling Opening: 8 1/4" x 8 1/4" No. of Stud Latches: 1
20-0030		Door Size W x H: 10" x 10" Wall Or Ceiling Opening: 10-1/4" x 10-1/4" No. of Stud Latches: 1
20-0012		Door Size W x H: 12" x 12" Wall Or Ceiling Opening: 12 1/4" x 12 1/4" No. of Stud Latches: 1
20-0003		Door Size W x H: 14" x 14" Wall Or Ceiling Opening: 14 1/4" x 14 1/4" No. of Stud Latches: 1
20-0014		Door Size W x H: 16" x 16" Wall Or Ceiling Opening: 16 1/4" x 16 1/4" No. of Stud Latches: 1
20-0016		Door Size W x H: 18" x 18" Wall Or Ceiling Opening: 18 1/4" x 18 1/4" No. of Stud Latches: 3
20-0018		Door Size W x H: 24" x 24" Wall Or Ceiling Opening: 24 1/4" x 24 1/4" No. of Stud Latches: 3