



Item P14-0738

Fiberglass Extension Ladders

Extra heavy duty extension designed for rugged jobsite conditions. Features flat-top, D-shape fully serrated rungs for safe standing. Heavy duty plated steel shoes with thick rubber tread can be used with tread down or in the spike position. Mar resistant rail end caps provide rail protection for longer life and protection of work surfaces. All sizes have a Type 1A (300 lb.) rating. Meets all OSHA requirements and the ANSI A14.5 standard.

*Does not include rope & pulley.

Item	Description	Attributes
14-0738		Total Length: 16' Length Each Section: 8' Max. Ext. Length: 13' Weight (lbs.): 34 Details: * Max Outside Width: 17 1/16"
14-0739		Total Length: 20' Length Each Section: 10' Max. Ext. Length: 17' Weight (lbs.): 45 Max Outside Width: 17 1/16"
14-0740		Total Length: 24' Length Each Section: 12' Max. Ext. Length: 21' Weight (lbs.): 53 Max Outside Width: 17 1/16"
14-0741		Total Length: 28' Length Each Section: 14' Max. Ext. Length: 25' Weight (lbs.): 62 Max Outside Width: 17 1/16"
14-0742		Total Length: 32' Length Each Section: 16' Max. Ext. Length: 29' Weight (lbs.): 72 Max Outside Width: 17 1/16"
14-0743		Total Length: 36' Length Each Section: 18' Max. Ext. Length: 32' Weight (lbs.): 84 Max Outside Width: 18 1/2"
14-0744		Total Length: 40' Length Each Section: 20' Max. Ext. Length: 35' Weight (lbs.): 92 Max Outside Width: 18 1/2"