



Item P26-0233
Firestop - Cast In Place

SpecSeal Cast-In Firestop Devices install on forms or deck in advance of the concrete pour to form factory-firestopped openings for plumbing and electrical penetrations. The devices install easily and quickly. Simply position the sleeves as required, fasten to the form and pour the concrete. The molded plastic body can be cut to adjust to the depth of the pour and is tough enough to resist the rigors of the concrete finishing process. A variety of accessories permit installation under many common construction conditions including variations in concrete depth and installation over pan decks. The unique chambered intumescent system expands rapidly in the event of fire to provide up to a three hour fire rating. A resilient gasket system seals against the propagation of smoke and provides additional protection against transient water exposure. [Deck adapter kits](#) and [extension tubes](#) available.

Item	Description	Attributes
26-0233		Model: CD200M Size: For 2" Metallic Pipe
26-0235		Model: CD300 Size: For 3" Plastic Pipe
26-0237		Model: CD300M Size: For 3" Metallic Pipe
26-0239		Model: CD400 Size: For 4" Plastic Pipe
26-0241		Model: CD400M Size: For 4" Metallic Pipe
26-0243		Model: CD600 Size: For 6" Plastic Pipe
26-0245		Model: CD600M Size: For 6" Metallic Pipe