



Item P10-9248

Honda EB Industrial Generators

Honda's legendary industrial generators have earned a reputation in the construction and rental industries for their incredibly rugged reliability. All EB series Honda generators come standard with full G.F.C.I. circuit protection for regulated job sites. All units were designed to meet OSHA requirements, making it ideal for worksite applications. Wide, positive lock folding handles offer convenient transport and storage and a more compact unit. CO-MINDER™ continuously monitors carbon monoxide (CO) levels. It automatically shuts down the generator before detected CO levels near the generator become dangerously high. Honda's exclusive iAVR technology ensures a consistent flow of power regardless of the load. No need to worry about power fluctuations ruining your valuable tools. Units come standard with a 2-wheel transport kit and lifting bar. The voltage selection switch allows for total generator output to be available through each of the 120 volt outlet for powering electric motors with large starting requirements (Output is limited to the rating of each receptacle). The Industrial Series uses Honda's GX series engines which are single cylinder, overhead valve, air-cooled.

| Item | Description | Attributes |
|---------|-------------|--|
| 10-9248 | | Model: EB5000 Watts: 5,000 Run Time per Tankful: 7.1 hrs.@ rated load, 10.5 hrs. @ 1/2 load Fuel Capacity: 6.2 gals Noise Level: 65 dB(A) @ rated load, 63 dB(A) @ 50% load Weight: 210.8 lbs. Electric Start: No |
| 10-9249 | | Model: EB6500 Watts: 6,500 Run Time per Tankful: 6.4 hr@ rated load, 9.8 hr @ 1/2 load Fuel Capacity: 6.2 gals Noise Level: 67 dB(A) @ rated load, 64 dB(A) @ 50% load Weight: 215.8 lbs. Electric Start: No |
| 10-9236 | | Model: EB10000 Watts: 10,000 Run Time per Tankful: 5.4 hrs @ rated load, 7.9 hrs @ 1/2 load Fuel Capacity: 8.1 gals Noise Level: 73 dB(A) @ rated load, 71 dB(A) @ 50% load Weight: 403 lbs. Electric Start: Yes |