



TOOLS & EQUIPMENT ■ SUPPLIES ■ SAFETY PRODUCTS ■ TOOL REPAIR ■ RENTALS

Item P16-0255

Lever Hoists

JET® JLP-A Series lever hoists combine safety, reliability, and durability that are designed to perform in light to medium-duty industrial applications. The patented Brake Wear Indicator increases safety by letting you know when to replace the friction disks. JET's improved easy free chain design is a two-step, no load, free chaining system. The system permits quicker hoist positioning and take up of slack chain, and is engineered not to free chain under load. The Weston style double ratchet pawl brake design splits the load to opposite sides of the ratchet gear for greater load security and increased safety. Industrial rated alloy steel hooks rotate 360° for easy rigging and slowly stretch to indicate an overload situation. Redesigned ergonomic grip allows for greater operator control and increased comfort. Secured with Allen screws and lock nuts, the cast-steel safety latches are more durable than stamped steel latches and will not bend out of compliance with lifting regulations. Grade 80 black oxide coated load chain for added durability. Needle bearings support the load sheave to increase efficiency and promote smooth operation. Impact resistant all steel construction for added durability and protection. This product complies with ANSI / ASME B30.21 and HST-3 Standards.

Item	Description	Attributes
16-0255		Capacity (Tons): 3/4 Lift: 10' Minimum Headroom: 12-4/5"
16-0256		Capacity (Tons): 3/4 Lift: 15' Minimum Headroom: 12-4/5"
16-0257		Capacity (Tons): 3/4 Lift: 20' Minimum Headroom: 12-4/5"