



Item P10-9819

M-5 Core Drilling System

Features an easy, quick disconnect motor mount reducing set up time and making horizontal hole drilling quicker and easier. Since the stand, wheel kit and switch box weighs only 52 lbs., the drill motor can be easily mounted for wall drilling once the stand is set in place. The M-5 stand is capable of drilling holes up to 12", and up to 20" with spacers and a hydraulic motor. Also has an angle drilling capability up to 45°. The column is constructed of anodized aluminum. 4-spoke sliding handle can be used on either side of the rig. Carrying handle allows portability and easy handling. **The M-5 Combination Rig includes a combination anchor/vacuum base, mast, carriage, control panel with amp meter and on/off switch, vacuum pump, ceiling jack, motor mount plate and your choice of drill motor.** The M-5 Anchor Rig has a smaller anchor base and does not include a vacuum pump. Select from the item numbers below.

Item	Description	Attributes
10-9819		Motor: 15 Amp Milwaukee RPM: 375/750 Safety Override: Shear Pin Details: M-5 Comb. Rig
10-9821		Motor: 20 Amp Milwaukee RPM: 300/600 Safety Override: Shear Pin Details: M-5 Comb. Rig
10-9823		Motor: 20 Amp Milwaukee RPM: 450/900 Safety Override: Shear Pin Details: M-5 Comb. Rig
10-9825		Motor: 20 Amp Milwaukee RPM: 450/900 Safety Override: Slip Clutch Details: M-5 Comb. Rig
10-9827		Motor: 20 Amp CB748* RPM: 350/900 Safety Override: Slip Clutch Details: M-5 Comb. Rig
10-9820		Motor: 15 Amp Milwaukee RPM: 375/750 Safety Override: Shear Pin Details: M-5 Anchor Rig
10-9822		Motor: 20 Amp Milwaukee RPM: 300/600 Safety Override: Shear Pin Details: M-5 Anchor Rig
10-9824		Motor: 20 Amp Milwaukee RPM: 450/900 Safety Override: Shear Pin Details: M-5 Anchor Rig
10-9826		Motor: 20 Amp Milwaukee RPM: 450/900 Safety Override: Slip Clutch Details: M-5 Anchor Rig
10-9793		Motor: M-5 Combination Drill Stand
10-9792		Motor: M-5 Anchor Drill Stand

*Replaces Black & Decker / DeWalt model