

## Item P15-0312

## Slip-on Buzz™ Nut

Can be installed at any desired position on the threaded rod, eliminats the need to thread hex nuts along the rod. Torque: 6 ft./lbs (8 Nm). Available in Zinc Plated or 316 stainless steel.

| Item    | Description | Attributes   |
|---------|-------------|--|
| 15-0282 |             | Thread Size: 1/4-20 Load (Ibs): 240 Zinc Plated: Yes Type 316 Stainless Steel: No          |
| 15-0284 |             | Thread Size: 3/8-16 Load (Ibs): 730 Zinc Plated: Yes Type 316 Stainless Steel: No          |
| 15-0286 |             | Thread Size: 1/2-13 Load (Ibs): 1,350 Zinc Plated: Yes Type 316 Stainless Steel: No        |
| 15-0288 |             | Thread Size: 5/8-11 Load (Ibs): 2,100 Zinc Plated: Yes Type 316 Stainless Steel: No        |
| 15-0310 |             | Thread Size: 1/4-20<br>Load (Ibs): 240<br>Zinc Plated: No<br>Type 316 Stainless Steel: Yes |
| 15-0311 |             | Thread Size: 3/8-16 Load (Ibs): 730 Zinc Plated: No Type 316 Stainless Steel: Yes          |
| 15-0312 |             | Thread Size: 1/2-13 Load (Ibs): 1,350 Zinc Plated: No Type 316 Stainless Steel: Yes        |