



Item P14-8080

Werner Type IA Fiberglass Two-Section Extension Ladder

Fiberglass Two-Section Extension Ladder has non-conductive rails making this ladder ideal for working near electricity. With a duty rating of 300lb, the ladder is durable and long lasting. The exclusive Alflo® rung joint means Twist-Proof® performance on the job. The Traction-Tred® D rungs are slip-resistant and the side rails are interlocking. The dual action feet are for use on hard or penetrable surfaces and swivel easily. The base and fly sections separate easily to use the base section as a single ladder. The durable rail shield bracket and shoe help protect the bottom of the rail. The fly section rails are pre-pierced at the top for easy field installation of accessories. Type IA Duty Rating 300 lb rating.

Item	Description	Attributes
14-8080		Size: 16' Max Open Extended Length: 13' Weight: 36.5 lbs
14-8081		Size: 20' Max Open Extended Length: 17' Weight: 44.5 lbs.
14-8082		Size: 25' Max Open Extended Length: 21' Weight: 52 lbs
14-8083		Size: 28' Max Open Extended Length: 25' Weight: 59.5 lbs
14-8084		Size: 32' Max Open Extended Length: 29' Weight: 71.5 lbs
14-8085		Size: 36' Max Open Extended Length: 32' Weight: 80.5 lbs
14-8086		Size: 40' Max Open Extended Length: 35' Weight: 88.5 lbs