

Item P29-1120

Dry Cut Diamond Core Bits

Dry diamond bit for coring holes in **block, brick, terra cotta and soft masonry** up to 5" diameter using an angle grinder. Cores a clean, neat hole in less than one minute with no spawling. 5/8"-11 standard thread with 9" drilling depth. **Not designed for use on solid concrete.** Designed to be used on a 7" or 9" 5,000 RPM angle grinder.

Item	Description	Attributes
29-1120		Diameter: 7/8" Power Tool Min. AMPS: 6 Power Tool Max. RPM/Min. RPM: 6,000/2,300
29-1121		Diameter: 1" Power Tool Min. AMPS: 6 Power Tool Max. RPM/Min. RPM: 6,000/2,300
29-1122		Diameter: 1 1/4" Power Tool Min. AMPS: 6 Power Tool Max. RPM/Min. RPM: 6,000/2,300
29-1123		Diameter: 1 1/2" Power Tool Min. AMPS: 7 Power Tool Max. RPM/Min. RPM: 5,000/1,600
29-1124		Diameter: 1 3/4" Power Tool Min. AMPS: 7 Power Tool Max. RPM/Min. RPM: 5,000/1,600
29-1125		Diameter: 2" Power Tool Min. AMPS: 7 Power Tool Max. RPM/Min. RPM: 5,000/1,200
29-1126		Diameter: 2 1/4" Power Tool Min. AMPS: 7 Power Tool Max. RPM/Min. RPM: 5,000/1,200
29-1127		Diameter: 2 1/2" Power Tool Min. AMPS: 7 Power Tool Max. RPM/Min. RPM: 5,000/1,200
29-1128		Diameter: 3" Power Tool Min. AMPS: 7 Power Tool Max. RPM/Min. RPM: 5,000/800
29-1129		Diameter: 3 1/2" Power Tool Min. AMPS: 10 Power Tool Max. RPM/Min. RPM: 5,000/800
29-1130		Diameter: 4" Power Tool Min. AMPS: 10 Power Tool Max. RPM/Min. RPM: 5,000/700
29-1131		Diameter: 5" Power Tool Min. AMPS: 10 Power Tool Max. RPM/Min. RPM: 3,500/700

29-1132		Diameter: 4 1/2" Power Tool Min. AMPS: 10 Power Tool Max. RPM/Min. RPM: 5,000/700
---------	--	--