



Item P20-0243

Fire Rated Access Doors - For Walls

Fire rated access door for **wall installation only**. Underwriters Laboratories rated for 1.5 hours, "B" label, and meets ANSI-UL 10B standard. Heavy duty spring closer assures positive latching when door closes. Concealed hinge, only door and frame is visible. Recessed exterior latch with ring operation. Interior latch release allows for door to be opened from the inside. Prime coated suitable for painting. Optional cylinder lock. **Other sizes and styles available, including stainless steel. Call for a complete listing. Manufactured by Elmdor.**

Item	Description	Attributes
20-0243		Door Size W x H: 8" x 8" Wall Opening: 8-3/8" x 8-3/8" No. of Stud Latches: 1
20-0244		Door Size W x H: 12" x 12" Wall Opening: 12-3/8" x 12-3/8" No. of Stud Latches: 1
20-0245		Door Size W x H: 14" x 14" Wall Opening: 14-3/8" x 14-3/8" No. of Stud Latches: 1
20-0246		Door Size W x H: 16" x 16" Wall Opening: 16-3/8" x 16-3/8" No. of Stud Latches: 1
20-0247		Door Size W x H: 18" x 18" Wall Opening: 18-3/8" x 18-3/8" No. of Stud Latches: 1
20-0248		Door Size W x H: 24" x 24" Wall Opening: 24-3/8" x 24-3/8" No. of Stud Latches: 2
20-0249		Door Size W x H: 36" x 36" Wall Opening: 36-3/8" x 36-3/8" No. of Stud Latches: 2