



Item P10-1605

Fluke 279 FC Thermal Multimeter

Full-featured multimeter with built-in thermal imager. 15 measurement functions including: AC voltage with low-pass filter, DC voltage, Resistance, Continuity, Capacitance, Diode test, Min/Max/Avg, AC current (with iFlex), Frequency. Thermal imaging reveals many electrical issues quickly and safely, eliminating the need for time-consuming testing and validation. Two-in-one tool is designed to increase productivity—no need to go back to the truck or office to retrieve a shared camera or wait for the thermographer—do more in less time! iFlex expands your measurement capabilities—get into tight, hard to reach spaces for current measurement (up to 2500 A AC). Designed for durability, built to withstand a 3 m (9.8ft) drop, double insulated with raised rubber holster for increased protection. Built-in Fluke Connect, transmit wirelessly to a smartphone and save time on reporting to validate work is complete. Includes: 18-inch iFlex flexible current probe, TL175 test leads, rechargeable lithium ion battery, charger, hanging strap and soft carrying case.

Specifications		
Voltage ac / dc	1000 V	
Range / Resolution	600.0 mV / 0.1 mV 6.000 V / 0.001 V 60.00 V / 0.01 V 600.0 V / 0.1 V 1000 V / 1 V	
Resistance	50 M?	
Frequency	100 KHz	
Capacitance	9999 ?F	
Safety Rating	CAT III 1000 V, CAT IV 600	
Length	8.5"	

Item	Description	Attributes
10-1605		Model: FLK-279 FC/iFlex