



TOOLS & EQUIPMENT ▪ SUPPLIES ▪ SAFETY PRODUCTS ▪ TOOL REPAIR ▪ RENTALS

**Item P20-0255**

**Fire Rated Uninsulated Access Door with Drywall Flange for Walls Only**

Not insulated and can only be used on fire rated walls, specifically those made of drywall. 16 gauge cold rolled steel. Not suitable where protection against temperature elevation is required. Self-latching tool-key operated latch and / or ring operated latch (both included). High quality with powder coated primer. Manufactured by Cendrex.

Item	Description	Attributes
20-0255		<b>Door Size:</b> 8" x 8" <b>Wall Opening:</b> 8-1/4" x 8-1/4"
20-0256		<b>Door Size:</b> 12" x 12" <b>Wall Opening:</b> 12-1/4" x 12-1/4"
20-0257		<b>Door Size:</b> 16" x 16" <b>Wall Opening:</b> 16-1/4" x 16-1/4"
20-0258		<b>Door Size:</b> 18" x 18" <b>Wall Opening:</b> 18-1/4" x 18-1/4"
20-0259		<b>Door Size:</b> 24" x 24" <b>Wall Opening:</b> 24-1/4" x 24-1/4"
20-0260		<b>Door Size:</b> 36" x 36" <b>Wall Opening:</b> 36-1/4" x 36-1/4"