



**Item P11-8285**

**Makita 1" Rotary Hammer, accepts SDSPLUS bits (DHandle)**

Powerful 7.0 AMP motor delivers 2 ft.lbs./2.7 j. of impact energy to handle the most demanding applications. 3-mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only" for multiple applications. One-touch sliding chuck for quick bit changes. Torque limiting clutch engineered to prevent gear damage by automatically disengaging gears if the bit binds. Variable speed trigger enables user to match the speed to the application for greater versatility. Ergonomic "D-shaped" handle with rubberized soft grip for increased comfort. Recessed lock-on button for continuous use. 40 bit angle settings allow the bit to be set at different positions for operating convenience. Extended life brushes are longer for more work between service intervals and less downtime. Sequential impact timing delivers timed hammering during rotation to minimize overlapping bit impacts for up to 50% faster drilling. Includes: side handle, depth gauge, and tool case.

Specifications	
Amps	7
No Load RPM	0 - 1,100 RPM
Max. Capacity (concrete drilling)	1"
Optimum Range (concrete drilling)	3/16" - 1/2"
Blows Per Minute (variable speed)	0 - 4,500 BPM
Impact Energy	2 ft. lbs.
Length	16-7/8"
Weight	6.6 lbs.

Item	Description	Attributes
11-8285	HR2475 1" Rotary Hammer, accepts SDSPLUS bits (DHandle)	