



Item P99-8136

TriggerFoam Pro™

TriggerFoam Pro™ Standard formula is a professional grade, gun applied, normal expansion, polyurethane foam sealant. Adheres to wood, metal, masonry and concrete. Seals gaps and joints, insulates, stops air infiltration and saves time and money. Ideal for use around pipes, wires and ductwork.

APPLICATIONS

Dispenses through a special gun that allows the user to control the flow rate and diameter of the bead for allowing precise placement of the foam. Voids should be filled approximately 30-40% to allow for the final expansion of the foam. Recommended curing time is 24 hours prior to scraping or painting.

TYPICAL USES

Insulating

- Floor / wall joints and openings • Electrical junction boxes • Attics • Refrigeration units and pipes
- Air conditioning systems

Filling

- Breaches in walls • Pipe penetrations in non-fire-rated walls • Voids in concrete forms • Underground utility ductwork • Sound dampening. • Stop and Go application product remains liquid in applicator until dispensed

Features

Easily adjustable applicator can dispense foam beads as small as 1/8"

High foam yield - up to 1.6ft³ per 29oz. can

Precision valve helps prevent pressure loss and prolongs shelf life

Hardened steel dispenser tip for longer life

Item	Description	Attributes
99-8136		Size: TriggerFoam Pro 29 oz. Std Box: 12